




**ENGINEERED
ELECTRONICS, INC.**

**ANNUNCIATOR
900-275**

FEATURES

- * 15 LED INDICATORS
- * BUZZER WITH VOLUME CONTROL
- * PLUG-IN CONNECTIONS
- * POWER ON INDICATOR
- * SURFACE OR FLUSH MOUNT
- * LAMP TEST



GENERAL

The 900-275 Annunciator can be used as a basic 15 LED indicator with common buzzer, a simple system with flash output, or visual indicator with 900-203 control panel for DS-2000 systems.

MOUNTING

FLUSH - 100-828 3 GANG BOX
SURFACE - 100-833 3 GANG BOX

POWER SUPPLY

900-826 24 Volts DC 2.5 Amp



ENGINEERED ELECTRONICS, INC. * 4301 INDUSTRIAL ACCESS ROAD * DOUGLASVILLE, GA. 30134

12/03/2008

JUMPERS

Buzzer controlled by Point input.
Shunt on H9 (1-2) only.

Buzzer intermittent
Shunt on H6 (1-2) and Flash Rate select (1-1) slow,
(2-2) mid, (3-3) fast. H-9 is to be left open.

Buzzer controlled by duty output from 900-203 control panel.
Shunt on H6 (1-2) only.

To activate lamp test insert small screwdriver through hole
above buzzer.

TYPICAL WIRING

